






FLEXILED SHE6 PW

Module mit 180 LED / Meter





Artikel-Nr.	Länge	Watt & Volt	Lichtfarbe	LED
1289001N/SHE	1000mm	14,4W @ 24Vdc	neutral weiß	180
1289001B/SHE	1000mm	14,4W @ 24Vdc	warm weiß	180
1289101N/SHE	2000mm	28,8W @ 24Vdc	neutral weiß	360
1289101B/SHE	2000mm	28,8W @ 24Vdc	warm weiß	360
1289201N/SHE	2500mm	36W @ 24Vdc	neutral weiß	450
1289201B/SHE	2500mm	36W @ 24Vdc	warm weiß	450
1289301N/SHE	3000mm	43,2W @ 24Vdc	neutral weiß	540
1289301B/SHE	3000mm	43,2W @ 24Vdc	warm weiß	540

LED-KONVERTER NICHT INBEGRIFFEN, BITTE EXTRA BESTELLEN



Lichtfarben warm weiß
Farbtemperatur 3100 Kelvin
Lichtausbeute 85 lm/W
CRI Ra ≥ 80



Lichtfarben neutral weiß
Farbtemperatur 4200 Kelvin
Lichtausbeute 85 lm/W
CRI Ra ≥ 80

* Beleuchtungsstärke niveau von FLEXILED SHE6 PW 1000mm

KEY FEATURES

Leistung	14,4W/m
Versorgung	24Vdc
LED / Meter	180
Teilbarkeit	3,3 cm (6 LED)
Schutz	IP20
Klebestreifen 3M®	nein
Kabel	200 cm
Stecker	Micro24

