






FLEXILED SHE6 PW

moduli da 180 LED/metro





| Codice | Lunghezza | Watt & Volt | Colore luce | LED |
|--------------|-----------|---------------|-----------------|-----|
| 1289001N/SHE | 1000mm | 14,4W @ 24Vdc | bianco naturale | 180 |
| 1289001B/SHE | 1000mm | 14,4W @ 24Vdc | bianco caldo | 180 |
| 1289101N/SHE | 2000mm | 28,8W @ 24Vdc | bianco naturale | 360 |
| 1289101B/SHE | 2000mm | 28,8W @ 24Vdc | bianco caldo | 360 |
| 1289201N/SHE | 2500mm | 36W @ 24Vdc | bianco naturale | 450 |
| 1289201B/SHE | 2500mm | 36W @ 24Vdc | bianco caldo | 450 |
| 1289301N/SHE | 3000mm | 43,2W @ 24Vdc | bianco naturale | 540 |
| 1289301B/SHE | 3000mm | 43,2W @ 24Vdc | bianco caldo | 540 |

ALIMENTATORE NON INCLUSO. DA ORDINARE SEPARATAMENTE.



Colore apparente bianco caldo
Temperatura colore 3100 Kelvin
Efficienza luminosa 85 lm/W
CRI Ra ≥ 80



Colore apparente bianco naturale
Temperatura colore 4200 Kelvin
Efficienza luminosa 85 lm/W
CRI Ra ≥ 80

* valori di illuminamento riferiti a FLEXILED SHE6 PW 1000mm

KEY FEATURES

| | |
|----------------------|----------------|
| Potenza | 14,4W/m |
| Alimentazione | 24Vdc |
| LED/metro | 180 |
| Divisibilità | 3,3 cm (6 LED) |
| Protezione | IP20 |
| Adesivo 3M® | no |
| Cavo | 200 cm |
| Connettore | Micro24 |

