





FLEXYLED SE H4
120 LED/metre modules

CE ENE IP44

Code	Lenght	Watt & Volt	Light colour	LED
1281501N/100	1000mm	12W @ 12Vdc	natural white	120
1281501B/100	1000mm	12W @ 12Vdc	warm white	120
1281501N/150	1500mm	18W @ 12Vdc	natural white	180
1281501B/150	1500mm	18W @ 12Vdc	warm white	180
1281501N/200	2000mm	24W @ 12Vdc	natural white	240
1281501B/200	2000mm	24W @ 12Vdc	warm white	240
1281501N/250	2500mm	30W @ 12Vdc	natural white	300
1281501B/250	2500mm	30W @ 12Vdc	warm white	300
1281501N/300	3000mm	36W @ 12Vdc	natural white	360
1281501B/300	3000mm	36W @ 12Vdc	warm white	360


LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.




Colour appearance warm white
Colour temperature 3100 Kelvin
Luminous efficiency 60 lm/W
CRI Ra ≥ 80

Colour appearance natural white
Colour temperature 4000 Kelvin
Luminous efficiency 60 lm/W
CRI Ra ≥ 80

* values referred to FLEXYLED SE H4 1000mm



Neither adhesives nor glue are required for FLEXYLED SE H4, because the soft silicone profile can be installed simply by pressing in the milled groove.



The standard configuration of FLEXYLED SE H4 comes with a 150mm power supply cable equipped with a Micro12 connector and 2m extension.

KEY FEATURES

Power	12W/m
Power supply	12Vdc
LED/metre	120
Divisibility	2,5 cm (3 LED)
Protection	IP44
Adhesive 3M®	no
Cable	15 cm + 200 cm
Connector	Micro12



For more information about accessories see page 56 e 62.