


**SKATE 3.0 slave**

Undercabinet LED luminaire

| Device with non-replaceable LED module

**Product features**

Housing:	thermoplastic polymers
Diffuser:	LGP ¹
Wiring:	2000mm
Connector:	Micro12
Switch	not included
N. LEDs:	24
Durability:	50,000 h ²

**Technical Data**

Wattage:	4 W
Voltage:	12 Vdc
Insulation degree:	III
Socket/Type:	LED

¹light guide plate²average value (minimum guaranteed complies with the requirements of EU Regulation 1194/2012)

Code	Watt & Volt	Light colour	Finish	EAN	Intrastat Number
1250510N/1	4W @ 12Vdc	natural white	aluminium	8027934237090	94054099
1250510B/1	4W @ 12Vdc	warm white	aluminium	8027934237137	94054099
Code	Watt & Volt	Light colour	Finish	EAN	Intrastat Number
1250519N/1	4W @ 12Vdc	natural white	steel	8027934235720	94054099
1250519B/1	4W @ 12Vdc	warm white	steel	8027934237144	94054099



Scan for installation manual



LED CONVERTER NOT INCLUDED. TO BE ORDERED SEPARATELY.polarized connector
for 12Vdc luminairefeeding by
constant voltage Converter

SKATE 3.0 slave

www.domusline.com

Undercabinet LED luminaire

| Device with non-replaceable LED module

**Marks and symbols**

Device in compliance with the EN60598 regulation-last edition.



Protection class III device. Power must be supplied by a safe power supply (in accordance with the EN61347-2-13 standard).





Device suitable for mounting in or on normally flammable surfaces.



Device only for indoor installation.



Device subject to the European Community directives 2002/96/CE and 2003/108/CE.

Photometric Data³

Colour appearance: natural white
 Color temperature: 3800 Kelvin
 Luminous flux: 155 lm
 Luminous efficiency: 40 lm/W
 CRI: Ra 80
 Binning: Variation of chromaticity coordinates within a MacAdam ellipse

Colour appearance: warm white
 Color temperature: 3000 Kelvin
 Luminous flux: 155 lm
 Luminous efficiency: 40 lm/W
 CRI: Ra 80
 Binning: Variation of chromaticity coordinates within a MacAdam ellipse


³average value (minimum guaranteed complies with the requirements of EU Regulation 1194/2012)

SKATE 3.0 slave

www.domusline.com

Undercabinet LED luminaire

| Device with non-replaceable LED module

Energy label

Scan for more info

Compliance

Standards : EN 60598-1:2009
 EN 60598-2-1:1997
 EN 62031:2009
 EN 55015:2008
 EN 61000-3-2:2007
 EN 61547:1996 + A1:2001
 EN 62471:2009
 EN 61000-3-3:1995 + A1:2001 + A2/IS1:2006

European Directives : 2014/35/EU Low Voltage
 2014/30/EU EMC
 2009/125/CE Erp (1194-2012-CE)
 2011/65/UE RoHS

Photobiological Safety: risk 0 (free)

Certificate/s:

Packaging data

	Pcs	Dimensions LxWxH (mm)	Gross weight	Net weight
Packaging unit:	1 pcs	210x100x80	0,29Kg	0,240Kg
Multibox unit:	10 pcs	400x290x250	3,55Kg	2,4Kg