


**SET SKATE 3.0 TLDM 3X**

Undercabinet SET LED luminaires

Device with non-replaceable LED module

**Product features**

Housing:	thermoplastic polymers
Diffuser:	LGP ¹
Wiring:	2000mm
Connector:	Micro12
LED Converter:	included
Switch:	dimmable TouchLed master
N. LEDs:	24
Durability:	50,000 h ²


Technical Data³

Wattage:	4 W
Voltage:	12 Vdc
Insulation degree:	III
Socket/Type:	LED

Code	Watt & Volt	Light colour	Finish	EAN	Intrastat Number
2234710N/2	3x4W @ 230Vac	natural white	aluminium	8027934235843	94054099
2234710B/2	3x4W @ 230Vac	warm white	aluminium		94054099
Code	Watt & Volt	Light colour	Finish	EAN	Intrastat Number
2234719N/2	3x4W @ 230Vac	natural white	steel	8027934235751	94054099
2234719B/2	3x4W @ 230Vac	warm white	steel		94054099



Scan for installation manual

LED CONVERTER INCLUDED.polarized connector
for 12Vdc luminaire**230V**feeding by
constant voltage Converter

Referred to SKATE 3.0 luminaires

Marks and symbols

Device in compliance with the EN60598 regulation-last edition.

Protection class III device. Power must be supplied by a safe power supply
(in accordance with the EN61347-2-13 standard).

Device suitable for mounting in or on normally flammable surfaces.








Device only for indoor installation.

Device subject to the European Community directives 2002/96/CE and
2003/108/CE.¹ light guide plate² average value (minimum guaranteed complies with the requirements of EU Regulation 1194/2012)³ referred to SKATE 3.0 luminaire

**SET SKATE 3.0 TLDM 3X**

Undercabinet SET LED luminaires

| Device with non-replaceable LED module

Scan for more info
about LED Converter**Photometric Data⁴**

Colour appearance:	natural white
Color temperature:	3800 Kelvin
Luminous flux:	155 lm
Luminous efficiency:	40 lm/W
CRI:	Ra 80
Binning:	Variation of chromaticity coordinates within a MacAdam ellipse
Colour appearance:	warm white
Color temperature:	3000 Kelvin
Luminous flux:	155 lm
Luminous efficiency:	40 lm/W
CRI:	Ra 80
Binning:	Variation of chromaticity coordinates within a MacAdam ellipse

⁴_average value (minimum guaranteed complies with the requirements of EU Regulation 1194/2012)

SET SKATE 3.0 TLDM 3X

www.domusline.com


Undercabinet SET LED luminaires

| Device with non-replaceable LED module

Configuration

In the TLDM configuration, SKATE 3.0 integrates a TouchLed electronic switch that turns on, off, and adjusts the brightness of the device with a "touch".

The switch also has a number of special features: auto-on safety switch-off and night light.

**Energy label**

Scan for more info

Compliance

Standards : EN 60598-1:2009 EN 55015:2006+A1:2007+A2:2009
 EN 60598-2-2:1997 EN 61547:2009
 EN 62031:2009 EN 61000-3-2:2006+A1:2009+A2:2009
 EN 62471:2008 EN 61000-3-3:2013

European Directives : 2014/35/EU Low Voltage
 2014/30/EU EMC
 2009/125/CE Erp (1194-2012-CE)
 2011/65/UE RoHS

Photobiological Safety: risk 0 (free)

Certificate/s:

Packaging data

	Pcs	Dimensions LxWxH (mm)	Gross weight	Net weight
Packaging unit:	1 pcs	250X200X100	0,952 Kg	0,814 Kg
Multibox unit:	12 pcs	530x290x350	12,342 Kg	9,768 Kg