


**SET SKATE 3.0 TLDM 5X**

Undercabinet SET LED luminaires

Device with non-replaceable LED module

**Product features**

Housing:	thermoplastic polymers
Diffuser:	LGP <sup>1</sup>
Wiring:	2000mm
Connector:	Micro12
LED Converter:	included
Switch:	Dimmable TouchLed master
N. LEDs:	24
Durability:	50,000 h <sup>2</sup>


**Technical Data<sup>3</sup>**

Wattage:	4 W
Voltage:	12 Vdc
Insulation degree:	III
Socket/Type:	LED

Code	Watt & Volt	Light colour	Finish	EAN	Intrastat Number
2234910N/2	5x4W @ 230Vac	natural white	aluminium	8027934237090	94054099
2234910B/2	5x4W @ 230Vac	warm white	aluminium	8027934237137	94054099
Code	Watt & Volt	Light colour	Finish	EAN	Intrastat Number
2234919N/2	5x4W @ 230Vac	natural white	steel	8027934235720	94054099
2234919B/2	5x4W @ 230Vac	warm white	steel	8027934237144	94054099



Scan for installation manual

**LED CONVERTER INCLUDED.**polarized connector  
for 12Vdc luminairefeeding by  
constant voltage Converter

Referred to SKATE 3.0 luminaires

**Marks and symbols**

Device in compliance with the EN60598 regulation-last edition.

Protection class III device. Power must be supplied by a safe power supply  
(in accordance with the EN61347-2-13 standard).

Device suitable for mounting in or on normally flammable surfaces.



Device only for indoor installation.

Device subject to the European Community directives 2002/96/CE and  
2003/108/CE.

1\_light guide plate






2\_average value (minimum guaranteed complies with the requirements of EU Regulation 1194/2012)

3\_referred to SKATE 3.0 luminaire

**SET SKATE 3.0 TLDM 5X**

Undercabinet SET LED luminaires

| Device with non-replaceable LED module

Scan for more info  
about LED Converter**Photometric Data<sup>4</sup>**

Colour appearance:	natural white
Color temperature:	3800 Kelvin
Luminous flux:	155 lm
Luminous efficiency:	40 lm/W
CRI:	Ra 80
Binning:	Variation of chromaticity coordinates within a MacAdam ellipse
Colour appearance:	warm white
Color temperature:	3000 Kelvin
Luminous flux:	155 lm
Luminous efficiency:	40 lm/W
CRI:	Ra 80
Binning:	Variation of chromaticity coordinates within a MacAdam ellipse

<sup>4</sup>\_average value (minimum guaranteed complies with the requirements of EU Regulation 1194/2012)

**SET SKATE 3.0 TLDM 5X**

www.domusline.com


Undercabinet SET LED luminaires

| Device with non-replaceable LED module

**Configuration**

In the TLDM configuration, SKATE 3.0 integrates a TouchLed electronic switch that turns on, off, and adjusts the brightness of the device with a "touch".

The switch also has a number of special features: auto-on safety switch-off and night light.

**Energy label**

Scan for more info

**Compliance**

Standards : EN 60598-1:2009 EN 55015:2006+A1:2007+A2:2009  
EN 60598-2-2:1997 EN 61547:2009  
EN 62031:2009 EN 61000-3-2:2006+A1:2009+A2:2009  
EN 62471:2008 EN 61000-3-3:2013

European Directives : 2014/35/EU Low Voltage  
2014/30/EU EMC  
2009/125/CE Erp (1194-2012-CE)  
2011/65/UE RoHS

Photobiological Safety: risk 0 (free)

Certificate/s:

**Packaging data**

	Pcs	Dimensions LxWxH (mm)	Gross weight	Net weight
Packaging unit:	1 pcs	250X130X60	1,316 Kg	1,178 Kg
Multibox unit:	12 pcs	530x290x350	16,71 Kg	14,136 Kg